

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Concrete Form Oil
Product Code:
Chemical Name: Motor Oil
Chemical Family: Blend
Manufacturer: Scot Lubricants of PA, Inc
 1801 E. Tremont Street
 P.O. Box 326
 Allentown, PA 18105

Emergency Telephone Numbers:
 Information: 610-433-2527 8am-5pm EST M-F
 CHEMTREC: 800-424-9300 24 hrs every day

2. COMPOSITION/INFORMATION ON INGREDIENTS

EXPOSURE GUIDELINES Component/CAS Number	LO%	HI%	OSHA		NFPA	
			TWA	STEL	TWA	STEL
LIMITS FOR THE PRODUCT						
SOLVENT-DEWAXED HEAVY PARAFFINIC DITILLATE (PETROLEUM)						
64742-65-0*		65 TO 99%				

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW
SLIGHTLY COMBUSTABLE
APPEARANCE: DARK AMBER FLUID **ODOR:** LUBE OIL ODOR
POTENTIAL HEALTH EFFECTS:
INHALATION: NO EFFECTS EXPECTED. **INGESTION:** PRACTICALLY NON-TOXIC.
EYE CONTACT: CONTACT WITH THE EYE CAUSES NO SIGNIFICANT EFFECTS.
SKIN CONTACT: MAY CAUSE SLIGHT IRRITATION WITH PROLONGED OR REPEATED CONTACT.
CARCINOGEN LISTED BY: IARC(N) NTP (NO) OSHA (NO) ACGIH (NO) OTHER (NO)

NFPA/HMIS CLASSIFICATION	HAZARD RATING
HEALTH – 0/0	0= LEAST 1=SLIGHT
FLAMMABILITY – 1/1	2=MODERATE 3=HIGH
REACTIVITY – 0/0	4=EXTREME
PERSONAL PROTECTION INDEX - X	

FIRST AID MEASURES

INHALATION: Move to fresh air.
EYE CONTACT: Flush with water for at least 15 minutes. If irritation persists, obtain medical assistance.
SKIN CONTACT: Wash with soap and water until no odor remains. If redness or swelling develops, obtain medical assistance. Wash clothing before reuse.
INGESTION: If large amounts are ingested, give large quantities of water, induce vomiting, and obtain medical assistance.

5. FIRE FIGHTING MEASURES

FLASHPOINT (METHOD): 420°F Minimum COC; 216°C Minimum COC

FLAMMABLE LIMITS: Not established

AUTO-IGNITION TEMP: 750°F Estimated; 359°C Estimated

EXTINGUISHING MEDIA: Dry chemical and CO₂. Foam and water fog are effective but may cause frothing.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Wear self-contained breathing apparatus. Wear structural firefighter's protective clothing. Cool tanks and containers exposed to fire with water.

6. ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Contain spill, advise EPA, state agency, if required. Absorb on inert material, shovel, sweep or vacuum spill.

7. HANDLING AND STORAGE

NFPA Class IIIB Storage. Wash thoroughly after handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Ventilate as needed to comply with exposure limit. General dilution ventilation acceptable.

PERSONAL PROTECTIVE EQUIPMENT —

EYE: Splash proof chemical goggles recommended to protect against splash of product.

GLOVES: Protective gloves recommended when prolonged skin contact cannot be avoided. The Impervious type is recommended.

RESPIRATOR: Concentration in air determines protection needed. Use only NIOSH certified respiratory protection. Respiratory protection usually not needed unless product is heated or misted. Half-mask air purifying respirator with dust/mist filters or HEPA filter cartridges is acceptable to 10 times the exposure limit. Full-face air purifying respirator with dust/mist filters of HEPA filter cartridges is acceptable to 50 times the exposure limit. Protection by air purifying respirators is limited. Use a positive pressure demand full-face supplied air respirator or SCBA for exposures above 50X the exposure limit. If exposure is above IDLH (immediately dangerous to life and health) or there is the possibility of an uncontrolled release or exposure levels are unknown then use a positive pressure demand full face supplied air respirator with escape bottle or SCBA.

OTHER: If contact is unavoidable, wear chemical resistant clothing. The following materials are acceptable as protective clothing materials: polyvinyl alcohol (PVA); polyvinyl chloride (PVC); neoprene; nitrile; viton; polyurethane; launder soiled clothes.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/ODOR: AMBER FLUID/MOTOR OIL ODOR.

VAPOR PRESSURE: <0.0001 (MM HG @ 20°C)

MOLECULAR WEIGHT: N/A (G/MOLE)

SOLUBILITY IN WATER: NIL (% BY VOLUME)

EVAPORATION RATE: 1000X SLOWER (ETHYL ETHER=1)

SPECIFIC GRAVITY: 0.86 (WATER=1)

VISCOSITY: 62.0 SUS @ 210°F 70.5 CST @ 40°C

BOILING POINT: HIGH

MELTING POINT: N/A

PACKING DENSITY: N/A

OCTANOL/WATER COEFF: N.D.

ODOR THRESHOLD: N.D.

VAPOR DENSITY: 10+ (AIR =1)

10. STABILITY AND REACTIVITY

STABILITY: Stable.

INCOMPATIBLE MATERIALS: Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: Combustion will produce carbon monoxide and asphyxiants.

11. TOXICOLOGICAL INFORMATION

FOR THE PRODUCT –

INHALATION: Low acute toxicity. **SKIN:** expected to be acutely non-toxic if absorbed. mild irritation with prolonged/repeated contact. **EYE:** mildly irritating on contact. **ORAL:** practically non-toxic

SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLEUM OIL – INHALATION: low acute toxicity. **SKIN:** practically non-toxic if absorbed may cause moderate irritation with prolonged and repeated contact. **EYE:** minimally irritating on contact. **INGESTION:** Practically non-toxic if swallowed.

ETHYLENE/PROPYLENE COPOLYMER: No data available for all routes of exposure

ZINC DIALKYL DITHIOPHOSPHATE: INHALATION: Toxic hydrogen sulfide is generated when heated above 200 deg. F. This can cause central nervous system (brain) effects, nausea, dizziness, confusion, loss of sense of smell, muscle cramps, in coordination, unconsciousness, coma, respiratory failure, or death. **SKIN:** Prolonged or repeated contact may cause moderate irritation, redness, drying, cracking, and dermatitis. **EYE:** Irritant. **ORAL:** Harmful if swallowed.

BORATED POLYISOSOBUTENYL SUCCINIC ANHYDRIDE –NO data available for all routes of exposure.

ACRYLIC COPOLYMER: No data available for all routes of exposure.

HYDROTREATED HEAVY PARAFFINIC PETROLEUM OIL: INHALATION: low acute toxicity. **SKIN:** practically non-toxic; if absorbed may cause moderate irritation with prolonged and repeated contact. **EYE:** minimally irritating on contact. **INGESTION:** Practically non-toxic if swallowed.

MAGNESIUM ALKYLARYL DETERGENT: NO data available for all routes of exposure. Possible skin and eye irritation with contact.

ALKYL DIPHENYLAMINE: No data available for inhalation or eye contact. **SKIN:** Possible allergic reaction. **ORAL:** Toxic if swallowed. May cause loss of appetite, diarrhea, & death.

POLYBUTENE: No significant effects by inhalation, skin absorption, or eye contact. **ORAL:** Practically non-toxic if swallowed

12. ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

13. DISPOSAL INFORMATION

Follow federal, state and local regulations. Not RCRA hazardous waste if uncontaminated. If “used”, RCRA criteria (ignitability, reactivity corrosivity, toxicity characteristics) must be determined. Do not flush to drain/storm sewer. Contract to authorized disposal service.

14. TRANSPORTATION INFORMATION

DOT

PROPER SHIPPING NAME Petroleum Lubricating Oil
 HAZARD CLASS: Not regulated
 ID NUMBER: Not regulated
 LABEL REQUIRED: Not regulated
 IMDG PROPER SHIPPING NAME: N.D.
 IATA PROPER SHIPPING NAME: N.D.

15. REGULATORY INFORMATION

TSCA: This product or all components of this product are listed on the U.S. TSCA inventory.

SARA 302 THRESHOLD PLANNING QUANTITY	N/A		
SARA 304 REPORTABLE QUANTITY	N/A		
SARA 311 CATEGORIES	Health	Immediate (Acute)	No
	Health	Delayed (Chronic)	No
	Physical	Fire	No
	Physical	Sudden Release of Pressure	No
	Physical	Reactive	No

When a product and/or component are listed below, the regulatory list on which it appears is indicated.

ZINC DIALKYL DITHIOPHOSPHATE – NJ 01

01=SARA 313	02= SARA 302/304	03=IARC CARCINOGEN
04=OSHA CARCINOGEN	05=ACGIH CARCINOGEN	06=NTP CARCINOGEN
07=CERCLA 302.4	08=WHMIS CONTROLLED PROD.	
10=OTHER CARCINOGEN		
PA=PA RTK	NJ=NEW JERSEY RTK	CA=CALIFORNIA PROP 65
MA=MASS. RTK	MI=MICHIGAN 406	MN=MINNESOTA RTK
FL=FLORIDA	RI=RHODE ISLAND	IL=ILLINOIS
NY=NEW YORK	WV=WEST VIRGINIA	CT=CONNECTICUT
LA=LOUISIANA	ME=MAINE	OH=OHIO

16. OTHER INFORMATION

Caution! Prolonged or repeated contact with used motor oil may be harmful to skin and could cause skin cancer. Promptly wash affected area with soap and water. WHMIS Classification: Not Controlled

SCOT LUBRICANTS OF PA, INC.
1801 E. TREMONT STREET
P.O. BOX 326
ALLENTOWN, PA 18105
610-433-2527

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of these data or the results to be obtained from the use thereof.